

Multilayer foams

Publication number: EP0922554 (A1)

Publication date: 1999-06-16

Inventor(s): ESCHENLAUER GEORGES [FR]; MASON JEFFREY JOHN [DE]; VAN VO CHAU [FR]

Applicant(s): DOW DEUTSCHLAND INC [DE]

Classification:






- **international:** *B29C47/88; B29C44/22; B29C44/46; B29C47/30; B29C47/88; B29C44/00; B29C44/34; B29C47/30; (IPC1-7): B29C44/46; B29C44/22*

- **European:** B29C44/22; B29C44/46D

Application number: EP19970121595 19971208

Priority number(s): EP19970121595 19971208

Also published as:

 EP0922554 (B1)
 US2002026977 (A1)
 US6440241 (B1)
 WO9929483 (A1)
 TW592930 (B)

more >>

Cited documents:

 US4192839 (A)
 WO9216363 (A1)
 GB1230978 (A)
 JP3293110 (A)
 JP8183082 (A)

Abstract of EP 0922554 (A1)

The present invention relates to foamed products and method for producing them, comprising a plurality of coalesced extruded layers or layers of coalesced strands of a foamed thermoplastic composition having a low density, by <a) providing at least one foamable composition comprising at least one polymer or copolymer and a blowing agent formulation, <b) extruding the composition through a die having a plurality of orifices, <c) foaming the extruded composition at a foaming temperature which is above the glass-transition temperature or the melting temperature of the polymer composition, <d) maintaining the foaming product at an elevated temperature for a sufficient period of time to obtain adhesion between individual foam layers, and <e) allowing the foamed product to cool, characterized in that a foamed product is obtained comprising a plurality of adherent foam layers,; wherein at least one of these foam layers extends across the whole breadth of the foamed product.

Data supplied from the esp@cenet database — Worldwide